

TECHNICAL FOCUS ON SLURRY TANKERS

# MODULO<sup>2</sup>

SIMPLE AND ROBUST WITH INTEGRATED CHASSIS

*Technical guide for making the right purchase*



**MODULO<sup>2</sup> 7000 ME**















**MODULO<sup>2</sup> 12000 MEB**

# JOSKIN<sup>®</sup>

# MODULO2

## A MODULAR RANGE

Standard ✓ or optional + equipment





✓

**Caps with arrows indicating any nut loosening**



+

**Side valve with automatic air inlet **A** for draining pipes when the valve is closed.**



✓

**Two Ø 2" hemispherical sight glasses (unlimited number, on request).**



+

**300 x 80 mm sight glass (unlimited number, on request).**



+

**Level indicator with proportional brakes**



+

**Fully transparent Ø 150 mm level indicator**



✓

**Inner baffles complying with EN707 safety standard (anti-pitching)**



+

**Tank counter**



+

**Automatic load transfer to the tractor during spreading.**  
 → Air inlet at the front of the tank  
 → Slurry release from the front of the tank



+

**Mountain discharge system with hydraulic device to take slurry at the front or rear.**



✓

**Ø 600 mm manhole with folding exact scatterer in compliance with CE standards. Perrot couplings.**



+

**MODULO 18000 ME**  
**Hinged rear door (Ø 850 mm)**



+

**18000 ME**  
**Hinged rear door (Ø 600 mm)**



+

**Pre-equipment for rear implement fitted directly to the tank (boom) or to a hydraulic linkage (boom or injector).**



✓

**3 pieces of pre-equipment for valve with Ø 150 mm or other (left, right and rear left on Ø 600 mm rear wall).**



+

**Adjustable Ø 150 mm outlet for limited positions at the rear of the tank.**



+

**Pre-equipment for Ø 150, 200 or 250 mm outlet with special location on request.**

## MORE INFORMATION? DISCOVER OUR OTHER TECHNICAL FOCUS FOLDERS

### VACUUM AND GARDA/JULIA PUMPS




Vacuum pump integrated into the drawbar to protect it and the tractor wheels.




Garda/Julia (centrifugal + vacuum pump).

### VOLUMETRIC AND CENTRIFUGAL PUMPS



Storm (centrifugal pump) only for discharge.




Spiral pump.



Hydraulic (A) or mechanical (B) upper filling door + ladder.


And much more!

### RUNNING GEAR



#### 3 brake types

- ✓ CE (A) Air brakes
- + (B) Hydraulic brakes
- + (C) Dual (hydraulic and air) brakes



Self-steering system when reversing and driving forward

And much more!

### ELECTROHYDRAULICS



Electro-hydraulic control

### FILLING ARMS



Pre-equipment for side filling arm (Ø 200 mm).




Pre-equipment for front JUMBO (pumping left and right).

# 17 MODULO2 MODELS

A SIMPLE, MODULAR AND VERSATILE SLURRY TANKER

Dimensions in mm. Total height on request (variable according to wheel Ø and options).



See our other technical focus folders: pumps, filling arms, electrohydraulic controls and running gears.

# JOSKIN



[www.joskin.com](http://www.joskin.com) • Rue de Wergifosse, 39 - 4630 Soumagne (Belgium)

E-mail: [info@joskin.com](mailto:info@joskin.com) • Tel.: +32 (0)4 377 35 45

August 2025. Non-contractual document. Data can be modified without prior notice. Pictures do not necessary correspond to the standard equipment.